

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **02302534 A**

(43) Date of publication of application: **14.12.90**

(51) Int. Cl.

F24F 3/16

(21) Application number: **01121231**

(22) Date of filing: **15.05.89**

(71) Applicant: **SHIMIZU CORP**

(72) Inventor: **YANO HISATO
HORIYAMA TAKESHI
HASHIMOTO SHUSUKE**

**(54) METHOD AND EQUIPMENT FOR SUPPLYING
PERFUME**


(57) Abstract:

PURPOSE: To vaporize a liquid perfume efficiently, to mix the perfume thereof with conditioned air and thereby to enable supply of it into a prescribed space by mixing the liquid perfume turned into a mist directly with the conditioned air in an air-conditioning duct.

CONSTITUTION: An ultrasonic oscillator 12 and a perfume injection nozzle in the fore end part of a perfume supply pipe 13 are disposed in an area of an air-conditioning duct 10 wherein an air stream is guided by a straightening plate 11. The air stream in the air-conditioning duct 10 is guided onto the plane of ultrasonic oscillation of the ultrasonic oscillator 12 by the straightening plate 11. When a micropump 14 is operated and thereby a liquid perfume in a perfume tank 15 is jetted from the perfume injection nozzle in the fore end part of the perfume supply pipe 13 onto the plane of ultrasonic oscillation of the ultrasonic oscillator 12, therefore, the liquid perfume is turned into a mist and the liquid perfume mist is scattered and vaporized. A mist particle of a large size which is not vaporized sufficiently is caught by a collision plate 18 and discharged through a drain pipe 19. Besides, the collision plate 18 disturbs the stream on the downstream

side in the air-conditioning duct 10 and thus facilitates diffusion of the vaporized liquid perfume in the air-conditioning duct 10.

COPYRIGHT: (C)1990,JPO&Japio





DEPATIS

Bibliographic data

Document JP0002302534AA (Patent)

Criterion	Field	Contents
Title	TI	[] METHOD AND EQUIPMENT FOR SUPPLYING PERFUME
Applicant	PA	SHIMIZU CORP
Inventor	IN	YANO HISATO ; HORIYAMA TAKESHI ; HASHIMOTO SHUSUKE
Application date	AD	15.05.1989
Application number	AN	121231
Country of application	AC	JP
Publication date	PUB	14.12.1990
Priority data	PRC PRN PRD	
IPC main class	ICM	F24F 3/16
IPC subclass	ICS	
IPC additional information on description	ICA	
IPC index class	ICI	
Abstract	AB	PURPOSE: To vaporize a liquid perfume efficiently, to mix the perfume thereof with conditioned air and thereby to enable supply of it into a prescribed space by mixing the liquid perfume turned into a mist directly with the conditioned air in an air-conditioning duct. CONSTITUTION: An ultrasonic oscillator 12 and a perfume injection nozzle in the fore end part of a perfume supply pipe 13 are disposed in an area of an air-conditioning duct 10 wherein an air stream is guided by a straightening plate 11. The air stream in the air-conditioning duct 10 is guided onto the plane of ultrasonic oscillation of the ultrasonic oscillator 12 by the straightening plate 11. When a micropump 14 is operated and thereby a liquid perfume in a perfume tank 15 is drawn from the perfume injection nozzle in the fore end part of the perfume supply pipe 13 onto the plane of ultrasonic oscillation of the ultrasonic oscillator 12, therefore, liquid perfume is turned into a mist and the liquid perfume mist is scattered and vaporized. A mist particle of a large size which is not vaporized sufficiently is caught by a collision plate 18 and discharged through a drain pipe 19. Besides, the collision plate 18 disturbs the stream on the downstream side in the air-conditioning duct and thus facilitates diffusion of the vaporized liquid perfume in the air-conditioning duct 10. COPYRIGHT: (C)1990,JPO&Japio

[Back to result list](#) | [Print](#) | [PDF display](#) | [Close](#)

© DPMA 2001